


End cap for mounting profile

Z-STU

The cap is used at the end of the "STU" mounting profiles. Improves the appearance of the ventilation system and protects the sharp ends of the profile.

Dimensions [mm]: 30x20, 30x30, 41x41





Hexagon steel nut, galvanised.

Dimensions [mm]

| Model | Diameter | Weight |
|-------|----------|--------|
| M8 | 8 | 10 kg |
| M10 | 10 | 10 kg |



Shock absorber/gasket for mounting profile **GA**

The shock absorber "GA" is used for mounting profiles "STU" as a protection against the vibrations transmission between the profile and the ventilation duct. Designed for profiles:

GA30 for STU profile 30 mm GA41 for STU profile 41 mm.



Galvanised, enlarged round washer

WWW



Round, galvanised, enlarged round washer.

Dimensions [mm]

| Model | Diameter | Weight |
|-------|----------|--------|
| M8 | 8 | 10 kg |
| M10 | 10 | 10 kg |

Galvanised washer **WW**



Round, galvanised washer.

Dimensions [mm]

| Model | Diameter | Weight |
|-------|----------|--------|
| M8 | 8 | 10 kg |
| M10 | 10 | 10 kg |



Galvanised bolt **BB**

Hexagon head screw, galvanised, metric thread over the entire length of the mandrel.

Dimensions [mm]

| Model | Diameter | Length | Weight |
|----------|----------|--------|--------|
| M8 x 25 | 8 | 25 | 10 kg |
| M8 x 50 | 8 | 50 | 10 kg |
| M8 x 60 | 8 | 60 | 10 kg |
| M10 x 25 | 10 | 25 | 10 kg |
| M10 x 40 | 10 | 40 | 10 kg |

Two-thread bolt

VDF



Two-thread bolt, for mounting brackets in walls and ceilings; galvanised steel.

Dimensions [mm]

| Model | Diameter | Length | Packaging |
|-----------|----------|--------|-----------|
| M8 x 120 | 8 | 120 | 100 pcs. |
| M10 x 100 | 10 | 100 | 100 pcs. |