



## Pressed reducer without gasket M/F **RCF**



Rounded, reinforced  
"SAFE" edges



Top quality  
galvanised steel  
275 g/m<sup>2</sup>




Double gasket,  
tightness class D

### Description

Pressed male and female reducer. Made from top quality galvanised steel (275 g/m<sup>2</sup>). Fully automated stamping process from one metal sheet. With every edge "SAFE" type - reinforced with curved rims, provide additional fitting rigidity and safe mounting. The version with gasket additionally includes double gasket EPDM clamped automatically - ensuring no risk of slipping during mounting. Product with tightness class D - every single bend undergoes air tightness test in the factory.


### Technical drawing RCF



### Dimensions RCF [mm]

ØD nom/Ød1 nom	L	H	kg	pcs/box	box type
100 / 80	110	40	0,11	72	P12
125 / 80	122	40	0,16	63	P12
125 / 100	112	45	0,17	63	P12
160 / 100	130	45	0,23	60	P6
160 / 125	117	45	0,21	60	P6
200 / 100	150	45	0,31	52	P6
200 / 125	137	45	0,30	45	P6
200 / 160	120	45	0,29	75	P4
250 / 160	144	45	0,42	90	P2
250 / 200	125	45	0,38	96	P2
315 / 160	177	45	0,63	56	P2
315 / 200	157	45	0,59	60	P2
315 / 250	132	45	0,52	52	P2

### Technical drawing RCFX



### Dimensions RCFX [mm]

ØD nom/Ød1 nom	L	H	kg	pcs/box	box type
100 / 80	105	35	0,11	84	P12
125 / 80	117	35	0,16	63	P12
125 / 100	107	40	0,16	63	P12
160 / 100	125	40	0,23	60	P6
160 / 125	112	40	0,21	60	P6
200 / 100	145	40	0,31	52	P6
200 / 125	132	40	0,30	45	P6
200 / 160	115	40	0,29	75	P4
250 / 160	139	40	0,42	90	P2
250 / 200	120	40	0,38	99	P2
315 / 160	172	40	0,63	52	P2
315 / 200	152	40	0,59	60	P2
315 / 250	127	40	0,52	65	P2



Packaging method on page 38